


Multimode 10Gig LC/SC Duplex Patch Cable

OM4



Product Overview

Fiber optic patch cords or jumpers are ideal for short distance patching applications. Fiber optic cable is made using exclusively Corning Optical Glass, within UL certified OFNR (Riser) rated jacket with Kevlar yarn. All fiber optic patch cables carry a Lifetime Warranty*

Performance Specifications

| | |
|-------------------------|-------------|
| Insertion Loss (max.): | 0.5dB |
| Storage Temperature: | -40°C +80°C |
| Operation Temperature: | -20°C +70°C |
| Mating Durability: | <0.2dB |
| Attenuation dB/km max.: | 1.0 |

Fiber Specifications

| | |
|--------------------------|-------------------|
| Wavelength: | 850nm/10Gig |
| Core Diameter: | 50µm |
| Cladding Diameter: | 125µm |
| Glass Buffer Size: | 900µm |
| Inner Strength Material: | Kevlar |
| Glass Type: | OM4 Infinicor SX+ |

Jacket Specifications

| | |
|---------------|----------------|
| Jacket Size: | 2mm |
| Jacket Style: | Duplex Zipcord |
| Jacket Color: | Aqua |
| Fire Rating: | OFNR (Riser) |

Connector Specifications

| | |
|----------------------|----------------|
| Connector Type (1): | LC/UPC |
| Connector Style(1):: | Duplex w/ Clip |
| Ferrule Type (1): | Ceramic |
| Connector Type (2): | SC |
| Connector Style (2): | Duplex w/ Clip |
| Ferrule Type (2): | Ceramic |

Ordering Specifications

| Part Number | Length (m) |
|----------------|-------------|
| GS-LCSC-xx-10G | xx = Length |

Lifetime Warranty: Limited to the replacement of the cable for manufacturers defect or performance defect. CP technologies will not be liable for any additional costs incurred for replacement of defective cable.

Stock FIBER CABLES

- Built to exceed industry standards
- Insertion loss and reflectance on all connectors are tested for optimum performance guarantee
- UPC—Ultra Polished Connectors
- Typical Shipping: 1-2 Business Days